

GSN	XQ-8H	Product Name	XQ-POWER 12V40kg-cm Hight Voltage Brushless Tail Servo	Model	XQ-RS8140H	Material	CNC all-metal case


Process flow

CNC / industry testing torque

SIZE OF THE DRAWINGS









The Drawings

Photos1



Photos2



Control Specifications

NO.	Standard Test Environment	
1-1	Temperature range	25℃±5℃
1-2	Humidity range	65%±10%
NO.	**Apply Environmental Condition**	
2-1	Storage Temperature Range	-20℃～70℃
2-2	Operating Temperature Range	-15℃～65℃
NO.	**Mechanical Specification**	
3-1	Servo Dimensions	20*40*38 mm
3-2	Servo Weight	78g
3-3	Servo Gear	Stainless Steel
3-4	Angle of limit	210°
3-5	Servo Bearing	2 Ball bearings
3-6	Output force shaft	25T-φ5.96mm
3-7	Servo arm	Plastic, POM
3-8	Case Material	Aluminium CNC
3-9	Servo line	300mm 22AWG
3-10	Built-in motor	Brushless motor
3-11	Splash water resistance	Yes
	Electrical Specification	
NO.	**Test Operating Voltage Range**	
4-1	**Work Voltage**	**7.4 V**
4-2	**No load speed**	0.11 sec/60°
4-3	**Runnig current (no load)**	320 mA
4-4	**Peak stall torque**	25 kg.cm
4-5	**Stall current**	2.8 A
	Work Voltage	**8.4 V**
4-6	**No load speed**	0.094 sec/60°
4-7	**Runnig current (no load)**	370 mA
4-8	**Peak stall torque**	29 kg.cm
4-9	**Stall current**	3.5 A
	Work Voltage	**12 V**
4-10	**No load speed**	0.07 sec/60°
4-11	**Runnig current (no load)**	440 mA
4-12	**Peak stall torque**	40 kg.cm
4-13	**Stall current**	4.0 A

AQL


Make table	CHECK	APPROVE
MR.ZHONG	MR.LIU	Manager.ZHOU

GSN	XQ-8H	Product Name	XQ-POWER 12V40kg-cm Hight Voltage Brushless Tail Servo	Model	XQ-RS8140H	Material	CNC all-metal case

Control Specification

Test display diagram

Photos1



Accessories

Photos1



Reference opinions of all departments: Agree

EMPHASIS

NO.	Item	Specification
5-1	Command signal	RS485
5-2	Amplifier type	Digital Controller
5-3	Pulse width range	800～2200 μsec
5-4	Neutral position	1520 μsec
5-5	Running degree	360° (when1000～2000 μsec) Customization
5-6	Dead band width	1 μsec
5-7	Rotating direction	CCW (when 1000～2000μsec)

Appearance inspection

NO.	QC details
5-7	Material qualified
5-8	Gear structure qualified
5-9	Function qualified
5-10	Use data qualified
5-11	Pass the test
NO.	**Other**
6-1	
6-2	
6-3	
6-4	

AQL

Other Accessories

7-1	Plastic arm bag
7-2	Screw
7-3	Metal arm (additional purchase)



Make table	CHECK	APPROVE
MR.ZHONG	MR.LIU	Manager.ZHOU